


# READERS WITH TRICOLOR LED

## CZ-3-M12 ATENA (xxx)



**Can work with any access control device,**


**Plastic casing with an M12 thread**

**Good solution for temperature and humidity loggers**

**Probe with tricolour RGB-LED, standard wire - 40 cm**

**Possibility to obtain 6 colours**

**Will work in Touch and Hold mode.**



WIRES	
	DATA
	GND
	RED LED
	BLUE LED
	GREEN LED
	COMMON LEAD

### Absolute Maximum Ratings at TA=25°C

Parameter	Blue	Hyper Red	Green	Units
Power dissipation	120	75	123	mW
DC Forward Current	30	30	30	mA
Peak Forward Current [1]	150	185	150	mA
Reverse Voltage	5			V
Operating Temperature	-40°C To +85°C			
Storage Temperature	-40°C To +85°C			

#### Notes:

1. 1/10 Duty Cycle, 0.1ms Pulse Width.

5. Casing	Plastic
6. Ring material	Ferrite steel + Cu + Ni + Cr <sub>3</sub>
7. Signal joint material	Brass + Ni +Cr <sub>3</sub>
8. Cable	6*0,14mm <sup>2</sup>
9. Fastening method	M20x1 screw
10. LED Kingbright	KPB-3025SURKCGKC
11. Work enviroment	Residential, commercial and lightly industrial
12. Working temperature	-40 °C do +85 °C
13. Humidity	Up to 70%

**DEMIURG W.WOJTASIK, R.WROŃSKA WOJTASIK, T.WOJTASIK s.c.**

**ul. Pustynna 66**

**93-479 Łódź**

**tel./fax: 042 636 70 70**